

LE-PRO 200-300 SERIES

BY REO-PURE™



A compact, energy efficient RO system designed to offer a feature-rich solution for many residential and light commercial applications. Engineered with the latest in membrane technology for increased efficiency and high-performance properties. This compact system is available as a stand-alone floor model, or wall mountable.

STANDARD FEATURES

- Sediment/Carbon Pre-Filtration
- Carbon Post-Filtration
- Pentek® 10" Slim Line Housings
- Product Water Pressure Shutoff Switch
- Pre-Filter Pressure Gauge, 0-100 PSI
- Post-Filter Pressure Gauge, 0-100 PSI
- Pump Pressure Gauge, 0-200 PSI
- Product Water Pressure Gauge, 0-100 PSI
- Pentek® Twist-to-Lock Membrane Housing
- Aquatec® High Flow Booster Pump
- Aquatec® Feed Water Solenoid Valve
- JG® Fittings and Tubing with Safety Locking Clips
- Factory Tested and Inspected for Top-Quality
- Designed and Assembled in the U.S.A.
- One Year Limited Warranty



MODEL	CAPACITY (GPD/GPM)	MEMBRANE	DESIGN RECOVERY	NOMINAL TDS REJECTION
LE-PRO 200	200 / 0.14	2" X 12" (QTY. 1)	40%	98%
LE-PRO 300	300 / 0.21	2" X 12" (QTY. 2)	50%	98%

REO-PURE™ LE-PRO 200-300 SERIES ORDERING GUIDE



ITEM NUMBER:

			#1				#2	#3	#4	#5
8	7	7				1	-		-	

#1 - GPD (SELECTION REQUIRED)

200 300

#2 - MOUNTING (SELECTION REQUIRED)

- 1 - Floor Stand Brackets
- 2 - Wall Mount Brackets

#3 - MONITOR

- 1 - TDS, Single Probe
- 2 - TDS, Dual Probe

#4 - FILTER HOUSINGS

- 1 - 20" Slim-Line - ONLY AVAILABLE W/ WALL MOUNT
- 2 - 10" Slim-Line w/ Calcite Post
- 3 - 10" Slim-Line w/ DI Post
- 4 - 20" Slim-Line w/ Calcite Post - ONLY AVAILABLE W/ WALL MOUNT
- 5 - 20" Slim-Line w/ DI Post - ONLY AVAILABLE W/ WALL MOUNT

#5 - VALVE OPTIONS

- 1 - Automatic Flush Valve
- 2 - TDS Blending Valve
- 3 - TDS Blending & Auto Flush Valve



LE-PRO 300
(Floor Model w/ TDS Blending Valve)