

LP3 225-1750 SERIES

BY REO-PURE™



A compact, energy efficient RO system designed to handle those most complex and demanding applications. Its rugged design delivers years of dependability and outstanding performance. The standard features incorporated into every system have been carefully selected to maximize water recovery, provide ease of installation, operation and maintenance, and ensure proper quality and quality of water.

STANDARD FEATURES

- Sediment/Carbon Pre-Filtration
- Pentek® 20" Slim Line Housings
- Low Feed Water Pressure Safety Switch
- Product Water Pressure Switch
- On/Off Standby Switch
- Feed Water Shutoff Ball Valve
- Water Saving Recirculation Loop
- Pre and Post Filter Pressure, Liquid Gauges
- Operating Pressure, Liquid Gauge
- Feed Water Solenoid Valve
- Fluid-O-Tech™ Rotary Vane Pump
- High Efficiency Carbonator Motor
- Manual Membrane Flush Valve
- Product Water Check Valve
- John Guest® Safety Locking Clips
- 115V, 60HZ, 1PH Electrical
- Powder Coated Aluminum Frame
- Factory Tested for Quality
- Assembled in the U.S.A.
- One Year Limited Warranty

OPTIMUM

with intelligent RO controller

- Automatic Membrane Flush
- Pretreatment Lockout
- Tank Full Indicator
- LED Status Indicators
- Field Selectable Programs
- Smooth Start/Stop Operations
- System Fault Notifications



MODEL	CAPACITY (GPD/GPM)	MEMBRANE	DESIGN RECOVERY	NOMINAL TDS REJECTION
LP3-225	225 / 0.16	2" X 12" (QTY. 1)	50%	98 - 99%
LP3-350	350 / 0.24	2.5" X 21" (QTY. 1)	50%	98 - 99%
LP3-500	500 / 0.35	2" X 26" (QTY. 1)	50%	98 - 99%
LP3-750	750 / 0.52	2.5" X 40" (QTY. 1)	50%	98 - 99%
LP3-1000	1,000 / 0.69	4" X 21" (QTY. 1)	50%	98 - 99%
LP3-1750	1,750 / 1.22	4" X 40" (QTY. 1)	50%	98 - 99%

REO-PURE™ LP3 225-1750 SERIES ORDERING GUIDE



ITEM NUMBER: #1 #2 #3 #4 #5 #6 #7 #8 #9

9 4 [] [] [] [] - [] - [] - [] - [] - [] - [] - []

#1 - MODEL (SELECTION REQUIRED)

- 1 - Standard
- 2 - Optimum

#2 - GPD (SELECTION REQUIRED)

0225 0350 0500
0750 1000 1750

#3 - MATERIAL (SELECTION REQUIRED)

- 1 - Standard*
- 8 - Stainless Steel
- 9 - Lead Free

#4 - MEMBRANE (SELECTION REQUIRED)

- 1 - Standard*
- 2 - Filmtec Standard[†]
- 6 - Filmtec NF270[†]
- 8 - Filmtec LCLE[†]

#5 - FILTER (SELECTION REQUIRED)

- 1 - Standard*

#6 - SHUTOFF TYPE (SELECTION REQUIRED)

- 1 - Product Pressure Switch*
- 2 - ATMO, No Float
- 3 - ATMO, Float Package

#7 - MONITOR

- 1 - TDS Push-to-Test, QC-1, Single Probe
- 2 - TDS Digital, SM-1, Single Probe
- 4 - TDS Digital, DM-2, Dual Probe

#8 - PACKAGING

- 3 - Export, Full Wooden Crate

#9 - CUSTOM OPTIONS

- 1 - Blending Valve, TDS, Includes Monitor



LP3-1750 Optimum
(Shown w/ Flexwave SSRO40 & Grundfos SCALA2)

* Designates a standard feature included with the base model

[†] Not available for all models



TEL: 262.634.2386 | TOLL FREE: 800.357.8538

FAX: 262.634.6259 | TOLL FREE: 888.700.6144

For items not listed, please call for additional information.

EMAIL: sales@greatlakesintl.com

WEB: greatlakesintl.com

03062026